

# **DESIGN CRITERIA**

Building Services - Permits 451 South State Street, Room 215 Salt Lake City, Utah 84111 Phone: (801) 535-6000

Effective 7/1/2023 Salt Lake City Corporation – Building Services, uses the following design criteria when reviewing a project or development within the corporate limits of Salt Lake City.

- 1. **BUILDING CODES:** Building Services enforces the following building codes with State amendments.
  - 2021 International Building Code (including Appendices C and J)
  - 2021 International Residential Code (including Appendices AE and AQ;)
  - 2021 International Plumbing Code
  - 2021 International Mechanical Code
  - 2021 International Fuel Gas Code
  - 2021 International Energy Conservation Code (commercial provisions)
  - 2021 International Existing Building Code
  - 2021 International Fire Code
  - 2020 National Electric Code
  - 2017 edition of ICC A117.1 Accessible and Useable Buildings and Facilities

#### 2. SNOW LOADS:

a) Ground Snow Loads: The actual snow loads vary depending upon elevation. For all projects located at, or below, 4,239 feet mean sea level the ground snow load (Pg) shall be a minimum of 28 pounds per square foot. For elevations above 4,239 feet mean sea level please visit <a href="https://utahsnowload.usu.edu">https://utahsnowload.usu.edu</a> as referenced in Section 15A of Utah's "State Construction and FireCodes Act"

b) **Roof Snow Loads:** Shall be determined per Chapter 7 of ASCE 7-16.

c) Seismic Snow: At locations where the roof snow load exceeds 30psf a percentage of the snow load must be considered in the effective seismic weight of the structure per Section 15A-3-107 of Utah's "State Construction and Fire Codes Act".

#### 3. WIND:

- a) Speed: All wind speeds listed below are 3-second gust at 33 feet above the ground.
  - Residential: 115 mph
  - Commercial (see IBC Figures 1609.3(1-4):
    - Risk Category I = 100 mph
    - Risk Category II = 105 mph
    - Risk Category III = 110 mph
    - Risk Category IV = 115 mph
- b) **Exposure:** Site specific (per Chapter 26 of ASCE 7-16). Typically "B" or "C".

URL: <a href="https://www.slc.gov/">https://www.slc.gov/</a>



## **DESIGN CRITERIA**

**Building Services - Permits** 451 South State Street, Room 215 Salt Lake City, Utah 84111

Phone: (801) 535-7752

### 4. SEISMIC:

a) Seismic Design Category:

Residential: D2 Commercial: D

- b) Site-specific: Because ground motions tend to vary substantially throughout the city, the mapped spectral accelerations (S<sub>S</sub> & S<sub>1</sub>) should be obtained by considering the site-specific address or latitude and longitude values and obtaining the ground motions from the Applied Technology Council's "ATC Hazards by Location" tool (https://hazards.atcouncil.org/).
- c) Site-Specific Parameters (unless ASCE 7 exceptions are met):
  - $S_1 \ge 0.2g$  and Site Class 'D or E'  $\rightarrow$  A ground motion hazard analysis (GMHA) must be provided
  - $S_S \ge 1.0g$  and Site Class 'E'  $\rightarrow$  A ground motion hazard analysis (GMHA) must be provided.
  - Site Class 'F'  $\rightarrow$  A site response analysis (SRA) must be provided.

#### 5. SOILS:

- a) Frost Depth: 30 inches.
- b) Site Class: Site specific. For projects not requiring a geotechnical report (see below) Site Class 'D' can be assumed per Section 20.1 of ASCE 7-16 but ground motions must be adjusted per IBC 1613.2.3.
- c) Allowable Bearing Pressures:
  - Foundation pressure: 1,500psf, per IRC Table R401.4.1 and IBC Table 1806.2.
  - Lateral pressure: 100psf/f, per IBC Table 1806.2.
  - The above listed values are maximum allowable values unless listed otherwise by a site-specific geotechnical report complying with IBC 1803.6 and IBC 1803.5.5, as applicable.

#### d) Site-specific Geotechnical Report:

- General: All geotechnical reports submitted for permit issuance must be dated no later than two years from the permit application date. Outdated reports must be accompanied by a letter from a qualified geotechnical engineer stating that the report requirements are still valid or stating what items may have changed.
- Residential: Residential projects meeting one or more of the following requirements must provide a site-specific geotechnical report meeting the requirements of IBC 1803.6:
  - Where the building footprint is greater than 3,000 square feet, or has a gross square footage of 6,000 square feet or greater; or
  - Where the grade supporting the structure has a slope equal to or greater than 20 percent; or
  - Where the building is to be built on a lot in which a previous structure once existed.
- Commercial: All commercial projects require a site-specific soils report meeting the requirements of IBC 1803.6 and IBC 1803.5.5, as applicable. Additions to existing facilities of less than 3,000 square feet are exempt from this requirement.



## **DESIGN CRITERIA**

**Building Services - Permits** 451 South State Street, Room 215 Salt Lake City, Utah 84111

Phone: (801) 535-7752

### 6. FLOOD HAZARDS:

- a) Flood Hazard Areas:
  - Residential: Buildings and structures located in flood hazard areas (i.e. Flood Zones A or V) must comply with IRC R322.
  - Commercial: Buildings and structures located in flood hazard areas must comply with IBC 1612, Chapter 5 of ASCE 7-16 and ASCE 24-14.
- b) Floodways: Buildings and structures located in identified floodways must be designed and constructed in accordance with ASCE 24-14.
- c) **Interactive Flood Zone Map:** Available at the following web link... https://www.arcgis.com/apps/webappviewer/index.html?id=03d70bc5fecc4278b4a747added 399a9
- 7. **RAINFALL:** Average annual rainfall is 16 inches.
- 8. CLIMATE ZONE: 5B
- 9. **WEATHERING:** Severe
- 10. **TERMITE:** None to Slight
- 11. WINTER DESIGN TEMP: 8°F
- 12. ICE SHIELD UNDERLAYMENT: Yes
- 13. AIR FREEZING INDEX:  $\leq 1500$
- 14. MEAN ANNUAL TEMP: 45°F

Last Revised: 07/2023